



Optional shoulder harness



Adjustable viewing angle



Antenna operated system




Optional antenna cart

1. Portable, in-the-box concept

2. Trans-reflective screen for maximum visibility

3. High frequency antennas

4. Transparent grid mat


 Scan, cut, and core
with confidence!

MALÅ CX System

Ground Penetrating Radar for Structural Investigations

The MALÅ CX Concrete Imaging System is an easy to use, Ground Penetrating Radar (GPR) system designed for the non-destructive investigation and imaging of concrete and other structure.

Construction professionals involved in the cutting, coring or drilling of concrete structure require a safe and reliable means of inspecting work areas to locate and identify hidden features that could cause damage to machinery, or pose a danger to the operator or the structure itself during these activities.

The MALÅ CX system allows you to scan concrete structure simply and safely in three different measurement modes; 2D-, 3D Grid- and Object Mapper- projects and present data clearly for real-time and in-the-box data acquisition, display and analysis. It is a quicker, safer and more cost effective option than competing systems or traditional radiographic testing methods.

With its simple user interface and large number of software features, the MALÅ CX System offers a unique powerful choice for your high frequency GPR investigations.

Main Applications



The MALÅ CX system is the tool of choice for those who need to quickly and easily investigate areas prior to cutting, coring or drilling. Other applications include:

- Concrete / Structure inspection
- Measure depth of cover or slab thickness
- Measure layer thickness
- Locate and map reinforcing support structure
- Locate non-metallic features, i.e. heating / water pipes
- Quality assessment & control
- Void detection

Specific Features

The product's simple yet ergonomic and field rugged design, intuitive user interface and clear display is testament to its success and it remains as the number one choice in its field.

- Minimal set-up for fast start-up
- LINUX operating system for fast and reliable processing
- Intuitive project driven GUI for enhanced work flow
- Stand-alone Windows processing software
- Project modes for 2D, 3D Grid and Object Mapper
- In-the-box processing to clear jobs on site
- Supports EM (50/60Hz) functionality
- Hyperbola fitting tool for velocity calibrations
- Full remote capabilities with the buttons on the antenna



System Configuration

The MALÅ CX system comes as standard in a portable field rugged case, but can also be used in conjunction with an optional shoulder harness for greater portability and flexibility of use, depending on the application and user requirements.

The MALÅ CX system was the World's first to combine GPR with the more common Electro-Magnetic (EM) technology by way of a fully integrated 50/60Hz sensor. This combination allows the detection of both metallic and non metallic objects and features, but also aids in the detection and location of metallic conductors energized with 50/60 Hz energy within the structure under investigation; thereby offering an additional element of safety to the system.

Technical Specification

Power supply: External 12V or Li-Ion 12V/12Ah battery

Operating time: 6h with battery pack

Operating temp: -20° to +50°C or 0° to 120 °F

Environmental: IP65

Display: 10.4" Color TFT Ultra-Hi-Brite or trans-reflective LCD

Dimensions: 56 x 46 x 26 cm / 22" x 18" x 10" (in-the-box)

Weight: 19.5 kg / 42.9 lbs (in-the-box, including antenna)

Antennas: The MALÅ CX system fully supports the MALÅ High Frequency (HF) Antenna range allowing the user to choose the best antenna for their given application and obtain unsurpassed accuracy and data clarity.

See MALÅ High Frequency (HF) Antennas sales sheet.

See our webpage for latest information

Corporate Headquarters

MALÅ Geoscience
Skolgatan 11, SE-930 70
Malå, Sweden
Phone: +46 953 345 50
Fax: +46 953 345 67
E-mail: sales@malags.com

Offices

USA: MALÅ Geoscience USA, Inc., 465 Deanna Lane, Charleston, SC 29492
Phone: +1 843 852 5021, Fax: +1 843 284 0684, E-mail: sales.usa@malags.com

China: MALÅ Geoscience (China), Room 2604, Yuan Chen Xin BLDG, No.12 Yu Min Road Chao Yang District, Beijing 100029
Phone: +86 108 225 0728, Fax: +86 108 225 0815, E-mail: sales@malags.com

Malaysia: MALÅ Geoscience (South East Asia), 9-B, Jalan Prima 9, Metro Prima, Kepong, 52100 Kuala Lumpur, Malaysia
Phone: +60 (0)3 6250 7351; Fax: +60 (0)3 6250 2072, E-mail: sales@malags.com

Australia: MALÅ Geoscience (Oceania), 4/105A Ben Boyd Road, Neytral Bay, NSW 2089, Australia
Phone: +61 438 278 902, Fax: +61 2 9908 1484, E-mail: sales@malags.com